



SCHEMATIC

- NOTES:
- ELECTRICAL:
- 1: RATED CURRENT: 0.2A Max.
  - 2: RATED VOLTAGE: 50V AC.
  - 3: CONTACT RESISTANCE: 30 MILLIOHMS Max. AFTER TESTING: 100 MILLIOHMS Max.
  - 4: INSULATION RESISTANCE: 100 MEGAOHMS Min.
  - 5: DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC Min.
- MECHANICAL:
- 1: INSERTION FORCE: 3N-30N.
  - 2: WITHDRAWAL FORCE: 3N-30N.
  - 3: DURABILITY: 100 CYCLES.
- ENVIRONMENTAL:
- TEMPERATURE RANGE: -20°C TO 60°C.



ANGLE	±5°	MODEL NAME: RCA-613	 广东正宝科技有限公司 GUANGDONG TRENPRO TECHNOLOGY CO., LTD.	TITLE: RCA PIN JACK DWG NO.: REV.: A	
63 < L	±0.5	(PART NO.)			
16 < L ≤ 63	±0.4	DESIGN: X.H.Wang	11/24'18	UNIT: mm	
4 < L ≤ 16	±0.3	CHECKED: L.W.Wu	11/24'18	VIEW: 5:1	
L ≤ 4	±0.2	See table		SCALE: SHEET: 1/1	
TOL TABLE:		See table		SIZE: A3	
THIS DOCUMENT IS THE PROPERTY OF TRENPRO TECHNOLOGY CO., LTD. NO PART THEREOF MAY BE REPRODUCED AND USED WITHOUT THE PRIOR WRITTEN CONSENT OF THE OWNER		QTY: /	APPROVED: X.Q.Hu	11/24'18	

REV.:	ECN NO.:	MODIFIED MARK:	APPROVED:
A		FIRST RELEASE	