




REV.	ECN NO.	MODIFIED MARK	APPROVED
A		FIRST RELEASE	



- NOTES:
- ELECTRICAL:
- 1:RATED CURRENT: 3A Max.
 - 2:RATED VOLTAGE: 50V AC.
 - 3:INSULATION RESISTANCE: 100 MEGAOHMS Min.
 - 4:Dielectric Withstanding Voltage: 1200 VAC Min.
- MECHANICAL:
- 1:WIRE IN HOLD FORCE 5N (20#WIRE) MIN
 - 2:INSPECTED VOLTAGE, AT THE SPEED OF 6-10S PER MINUTES, THE SAMPLES ARE INSPECTED 10000 CYCLES, BUT THERE ARE NO DAMAGE ON THE PRESSURE AND THE RISING TEMPERATURE, ETC.
 - 3:APPLY 2kgf FORCE AT ANY DIRECTION , THERE NO LOOSE & NO CRACK

ANGLE	±5°	MODEL NAME: WP4-2B (PART NO.)	TITLE: WP PUSH TERMINAL
63 < L	±0.5	DESIGN: X.H.Wang 11/06'18	DWG NO.:
16 < L ≤ 63	±0.4	CHECKED: L.W.Wu 11/06'18	UNIT: mm
4 < L ≤ 16	±0.3	QTY: /	VIEW:
L ≤ 4	±0.2	APPROVED: X.Q.Hu 11/06'18	SCALE: 5:1
TOL TABLE:			SHEET: 1/1
THIS DOCUMENT IS THE PROPERTY OF TERPRO TECHNOLOGY CO., LTD. NO PART THEREOF MAY BE REPRODUCED AND USED WITHOUT THE PRIOR WRITTEN CONSENT OF THE OWNER			SIZE: A3

