






REV.	ECN NO.	MODIFIED MARK	APPROVED
A	—	FIRST RELEASE	



PCB LAYOUT
TOP VIEW



NOTES:
ELECTRICAL:
1: RATED CURRENT: 3A Max.
2: RATED VOLTAGE: 50V AC.
3: INSULATION RESISTANCE: 100 MEGAOHMS Min.
4: DIELECTRIC WITHSTANDING VOLTAGE: 1200 VAC Min.
MECHANICAL:
1: WIRE IN HOLD FORCE 5N (20#WIRE) MIN
2: INSPECTED VOLTAGE, AT THE SPEED OF 6-10S PER MINUTES, THE SAMPLES ARE INSPECTED 10000 CYCLES, BUT THERE ARE NO DAMAGE ON THE PRESSURE AND THE RISING TEMPERATURE, ETC. 3: APPLY 2kgf FORCE AT ANY DIRECTION, THERE NO LOOSE & NO CRACK

ANGLE	±5°	MODEL NAME: WP8-11	 广东正宝科技有限公司 GUANGDONG TRENPPO TECHNOLOGY CO., LTD.
63 < L	±0.5	(PART NO.)	
16 < L ≤ 63	±0.4	DESIGN: X.H.Wang 11/06'18	TITLE: WP PUSH TERMINAL
4 < L ≤ 16	±0.3	MAT'L: See table	DWG NO.:
L ≤ 4	±0.2	FINISH: See table	REV.: A
TOL TABLE:		Q'TY: /	APPROVED: X.Q.Hu 11/06'18
THIS DOCUMENT IS THE PROPERTY OF TRENPPO TECHNOLOGY CO., LTD. NO PART THEREOF MAY BE REPRODUCED AND USED WITHOUT THE PRIOR WRITTEN CONSENT OF THE OWNER		UNIT: mm	VIEW: 
		SCALE: 5:1	SHEET: 1/1
			SIZE: A3